


# KT15 Commercial Series: Bifold Door Track & Hardware

**MAXIMUM DOOR WEIGHT:** 120 lbs (55 kg) per bi-fold door (2 leaves)



**MIN & MAX DOOR THICKNESS:** 3/4" (19mm) to 1-3/4" (44.45mm)

**MAXIMUM CAPACITY:** Max leaf width = 24" (609mm). Max door height = 96" (2834mm). For door leaves over 18" (457mm) wide and or over 33 lbs (15 kg) in weight, bottom guiding system must be used.

**VERTICAL ADJUSTMENT:** 1/4" (6mm)

**TRACK:** Extruded aluminum, mill finish.

**HANGER / PIVOTS:** Steel carrier, plated, 4 nylon wheels, ball bearing. Pivots are steel and nylon.

**OPTIONS:** KT20 extruded aluminum floor channel, with KT120 steel plate, nylon swivel guide

**HARDWARE KITS:** KT15KIT-2L for 2 leaf application KT15HANGER (1 ea), KT15PIVOT (1 ea) top and bottom pivots, KT189 (1 ea) knob, KT155 (1 ea) wrench, installation sheet plus all screws.

**NOTE:** For multiple leaves folding to one side use one KT15KIT-2L for the first 2 leaves and for each additional 2 leaves add one KT15HANGER & one KT189 bifold door knob.

